



SCHOOL COURT - MULTI USE GAMES AREA SPECIFICATION

All AXO LEISURE Ltd. Multi use games areas are designed to meet the requirements of BS EN 15312. All structural steel components are made from mild steel conforming to BSEN 10210 and BSEN 10219 respectively.

METAL TREATMENT

All Posts, Panels and Gates etc. are galvanised to BS EN ISO 1461. An architectural quality BS6497, polyester powder coatings follows, itself reaching a thickness of between 70-100 microns. The result is a smooth, attractive, hard wearing and weather resistant finish.

POSTS/CROSSBARS

80 x 40 x 3.2mm Rectangular hollow section with fully welded end caps. (Goal posts 100mm x 100mm for added strength)

INFILL PANELS

Flow forge – horizontal flat bar (25mm x 3mm) and vertical twisted bar 6mm diameter.

Grid size 100mm x 41mm x 25mm wide.

Flow forge panels are framed top and bottom with 25x25x3.2mm square hollow section with fully welded end caps to form handrail.

Standard panel pitches: 1m, 1.25m 1.5m, 2m,

Curved panel option for corners or chicane entrances

GOALS

Goal areas are 1m x 2.4m

Fully enclosed curved goal backs to prevent ball escape

BACK BOARDS

19mm black and white polyethylene u.v. resistant. Manufactured to BS EN 15312 requirements.

FIXINGS

All fixings are zinc plated bolts and nyloc nuts, protected with polypropylene tamper resistant cover caps, providing a high level of security.

INSTALLATION

Slotted lugs on infill panels allow some variations in levels for ease of installation and irregular size levels.

STANDARD COLOURS

Colours available from the RAL range, fully customizable court colour combinations to suit your school, authority or teams colours.

