

KEY POINTS

- FULLY WELDED GRID MESH SYSTEM FOR LOW IMPACT NOISE
 - ANTI CLIMB PANELS
- TOP AND BOTTOM RAILS FOR RIGIDITY
- ANTI-TAMPER FIXINGS & COVER CAPS
- 25 YEAR STRUCTURAL GUARANTEE

All AXO LEISURE Ltd. Multi use games areas are designed to meet the requirements of BS EN 15312. All structural steel components are made from mild steel conforming to BSEN 10210 and BSEN 10219 respectively.

METAL TREATMENT

All Posts, Panels and Gates etc. are galvanised to BS EN ISO 1461. An architectural quality BS6497, polyester powder coatings follows, itself reaching a thickness of between 70-100 microns. The result is a smooth, attractive, hard wearing and weather resistant finish.

POSTS/CROSSBARS

100x100x4mm Square hollow section with fully welded end caps.

ANTI-CLIMB INFILL PANELS

Vertical flat bar (25mm x 3mm) and horizontal twisted bar 6mm diameter form a perfect anti-climb panel. Grid size 100mm x 41mm x 25mm wide.

Flow forge panels are framed top and bottom with 80x40x3.2mm Rectangular hollow section with fully welded end caps.

Standard panel pitches: 1m, 1.2m 1.5m, 2m, 2.2m Curved panel option for corners or chicane entrances **GOALS**

Goal areas are 6' x 12' (1.8m x 3.6m) to meet FA approved 'Mini soccer' goal size.

Goal backs available in a number of designs including curved, square, bully escapes, DDA access, gated, open or enclosed.

BACK BOARDS

19mm black and white polyethylene u.v. resistant. Manufactured to BS EN 15312 requirements. basketball hoops include chains with lower rings.

FIXINGS

All fixings are zinc plated bolts and nyloc nuts, protected with polypropylene tamper resistant cover caps, providing a high level of security.

INSTALLATION

Slotted lugs on both infill panels and posts allow some variations in levels and post pitches for ease of installation.

STANDARD COLOURS Colours available from the RAL range, fully customizable court colour combinations to suit your school, authority or teams colours.