

PRO-LITE COURT - MULTI USE GAMES AREA SPECIFICATION

All AXO LEISURE Ltd. Multi use games areas are designed to meet the requirements of BS EN 15312. All structural steel components are made from mild steel conforming to BSEN 10210 and BSEN 10219 respectively.

METAL TREATMENT All Posts, Panels and Gates etc. are galvanised to BS EN ISO 1461. An

architectural quality BS6497, polyester powder coatings follows, itself reaching a thickness of between 70-100 microns. The result is a smooth, attractive, hard wearing and weather resistant finish.

POSTS/CROSSBARS 80 \times 40 \times 3mm Rectangular hollow section with end caps.

INFILL PANELS Mesh aperture: 50 x 200mm or 50mm x 67mm (Sport rebound)

Wire diameter: twin 8mm horizontal, 6mm vertical (twin horizontal

wires)

Height: 1.8m, 1.2m or 3m Width: 2.51m standard

GOALS Goal areas are 6' x 12' (1.8m x 3.6m) to meet FA approved 'Mini

soccer' goal size.

Goal backs available in a number of designs including curved, square, bully escapes, DDA access, gated, open or enclosed.

Note: Goal posts and fencing to match Pro-Lite fencing specification or can be substituted for heavy duty Pro Court

specification

BACK BOARDS 19mm black and white polyethylene u.v. resistant. Manufactured to

BS EN 15312 requirements.

FIXINGS Galvanised steel fixing bracket & M8 self-tapping security head

screw.

STANDARD COLOURS Colours available from the RAL range, fully customizable court colour

combinations to suit your school, authority or teams colours.

