

KEY POINTS

- WELDED MESH SYSTEM
 VERSATILE INSTALLATION ON UNEVEN GROUND LEVELS
 - ANTI-TAMPER FIXINGS
- 10 YEAR STRUCTURAL GUARANTEE

All AXO LEISURE Ltd. Multi use games areas are designed to meet the requirements of BS EN 15312. All structural steel components are made from mild steel conforming to BSEN 10210 and BSEN 10219 respectively.



METAL TREATMENT

All Posts, Panels and Gates etc. are galvanised to BS EN ISO 1461. An architectural quality BS6497, polyester powder coatings follows, itself reaching a thickness of between 70-100 microns. The result is a smooth, attractive, hard wearing and weather resistant finish.

POSTS/CROSSBARS

 $80 \times 40 \times 3$ mm Rectangular hollow section with end caps. $80 \times 60 \times 3$ mm (over 3m high)

100 x 50 x 3mm (over 4m high)

INFILL PANELS

Mesh aperture below 1.2m : 50 x 67mm (sport rebound) and 50 x 200mm (above 1.2m)

Wire diametwer: TWIN 8mm horizontal, 6mm vertical

Height: 1m to 5m

Width: 2.52m standard post pitch

GOALS (if applicable)

Goal areas are $6' \times 12'$ (1.8m $\times 3.6$ m) to meet FA approved 'Mini soccer' goal size.

Goal backs available in a number of designs including bully escapes, DDA access, gated, open or enclosed.

BACK BOARDS (if applicable)

19mm black and white polyethylene u.v. resistant. Manufactured to BS EN 15312 requirements. basketball hoops include chains with lower rings.

FIXINGS

Galvanised steel fixing brackets & M8 self-tapping tri-lobal bolts which give vibration resistance when joining the panels to the steel posts.

Drive bit is unique to the bolt enhancing the security.

INSTALLATION

Panels can be clamped at varying heights for for ease of installation when ground conditions are not level.

STANDARD COLOURS Colours available from the RAL range, fully customizable court colour combinations to suit your school, authority or teams colours.